## Sto StoCretec

## Technical Data Sheet **StoBallotini Ø 75-150 μm**

Solid glass beads for slip resistance Ø 75 - 150  $\mu m$ 



Area of application	<ul> <li>as an admixture to StoPox or StoPur products in accordance with the relevant Technical Data Sheet</li> </ul>		
Properties	<ul> <li>transparent solid glass beads as extenders to achieve slip-resistant sealed surfaces</li> </ul>		
Appearance	• transparent		
Application			
Application	by roller, add to the total mixture		
Delivery			
	Article number	Name	Container
	14505-003	Sto Ballotini 75-150 µm	5 kg pail



## Technical Data Sheet StoBallotini Ø 75-150 μm

## **Special notes**

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

StoCretec GmbH Gutenbergstr. 6 D-65830 Kriftel

Tel.: +49 6192 401-104 Fax: +49 6192 401-105 stocretec@sto.com www.stocretec.de

Rev. no.: 1 / EN /StoCretec./. 30.11.2017 / PROD1147 / StoBallotini Ø 75-150 µm