

Technical Data Sheet

StoDivers EV 100

Cleaning agent for EP and PUR systems



Characteristics

Area of application • as a cleaning agent for tools soiled with epoxy resin or polyurethane resin

Properties • free from CFCs
• high cleaning efficiency

Technical data

Criterion	Standard / test specification	Value/ Unit	Notes
Density	DIN 53217	0.87 g/cm ³	g/cm ³ = kg/l
The characteristic values stated are average values or approximate values. Due to the natural raw materials in our products, the stated values can vary slightly in the same delivery batch; this does not affect the suitability of the product for its intended use.			

Application

Application

For application, see the Technical Data Sheets of the products where StoDivers EV 100 is used.

Note:

Adding StoDivers EV 100 to StoPox or StoPur products in order to decrease their viscosity requires the written permission of the supplier.

Adding cleaning agents can have a negative effect on the material's properties and appearance.

Notes, recommendations, special information, miscellaneous

General application instructions are available at www.stocretec.de and in the notes of the latest Technical Manual.

Delivery

Packaging Can

Article number	Name	Container
14409-002	StoDivers EV 100	20 kg can

Technical Data Sheet

StoDivers EV 100

	14409-001	StoDivers EV 100	8 kg can
Storage			
Storage conditions	Store in dry and frost-free conditions. Protect from direct sunlight.		
Storage life	In the original container until ... (see packaging).		
Identification			
Product group	Cleaning agents		
Safety	This product is subject to compulsory labelling in accordance with the current EU regulation. You will receive an EU Safety Data Sheet with your first order. Please observe the information regarding the handling of the product, its storage, and disposal.		
Special notes			
The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use. Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products. When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.			

StoCretec GmbH
Gutenbergstr. 6
D-65830 Kriftel

Tel.: +49 6192 401-104
Fax: +49 6192 401-105
stocretec@sto.com
www.stocretec.de