

Technical Data Sheet

StoDivers LB 100

Conductive copper tape, tin-plated



Characteristics

Application • for the connection to the ring line on electrically conductive floor coatings

Properties • self-adhesive

Format • Width: 12 mm
• length: 16.5 m

Technical data

Criterion	Standard / test regulation	Value/ Unit	Notes
-----------	----------------------------	-------------	-------

The characteristic values stated are average values or approx. values. We use natural raw materials in our products, which means that the stated values can vary slightly in the same delivery batch; this does not affect the suitability of the product for its intended use.

Substrate

Application

Consumption Execution Approx. consumption

loose, width: 12 mm, length: 16.5 m

Material consumption depends on the application, substrate and consistency, amongst other factors. The specified consumption values are only to be used as a guide. If required, precise consumption values should be determined on the project.

Application

Delivery

Article number	Designation	Container
03044-002	StoDivers LB 100	1 piece

Storage

Certificates / approvals

Identification

Technical Data Sheet

StoDivers LB 100

Special instructions

The information or data serves to ensure the product's intended use or its suitability for use and is based on our findings and experience. Nevertheless, users are responsible for establishing the suitability of the product for its intended use.

Applications other than those explicitly mentioned in this technical data sheet are only permissible after prior consultation. Where no approval is given, such applications are at the risk of the user. This applies particularly to combinations with other products.

When a new technical data sheet is published, all previous technical data sheets are no longer valid. The latest version is available on the Internet.

StoCretec GmbH
Gutenbergstr. 6
D-65830 Kriftel

Tel.: +49 6192 401-104
Fax: +49 6192 401-105
stocretec@sto.com
www.stocretec.de