

# Technical Data Sheet

## StoSeal P 305

Primer for StoSeal F 355 and StoSeal F 505



### Characteristics

<b>Area of application</b>	<ul style="list-style-type: none"><li>to ensure a force-transmitting and durable bond between the sealant and the joint flanks</li></ul>
<b>Properties</b>	<ul style="list-style-type: none"><li>very good adhesive bond to the substrate</li></ul>
<b>Information/notes</b>	<ul style="list-style-type: none"><li>for PUR coatings and non-absorbent substrates</li></ul>

### Application

#### Application

Using a paint brush, apply the undiluted primer evenly and not too thickly to the joint flanks.

Consumption: approx. 0.01 l/m

Then insert Sto-Backing Rod.

Following a flash-off time of 10 minutes (StoSeal P 305) (+23 °C), apply StoSeal F 355 or StoSeal F 505.

### Delivery

#### Packaging

tin

Article number	Name	Container
01828-004	StoSeal P 305	1 piece tin

### Identification

#### Safety

This product is subject to compulsory labelling in accordance with the current EU regulation.  
Observe the Safety Data Sheet!

# Technical Data Sheet

---

## StoSeal P 305

### Special notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use. Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

StoCretec GmbH  
Gutenbergstr. 6  
D-65830 Kriftel

Tel.: +49 6192 401-104  
Fax: +49 6192 401-105  
stocretec@sto.com  
www.stocretec.de