

Technical Data Sheet StoSeal P 505

Primer for StoSeal F 355 and StoSeal F 505



Characteristics			
Area of application	 to ensure a force-transmitting and durable bond between the sealant and the joint flanks 		
Properties	 very good adhesive bond to the substrate 		
Format	one tin contains 1 litre		
Information/notes	 for epoxy resin coatings and absorbent substrates, e.g. concrete 		
Application			
Application	Using a point bruch, apply the undiluted primer eventy and not too thickly to the		
	Using a paint brush, apply the undiluted primer evenly and not too thickly to the joint flanks.		

Consumption: approx. 0.01 l/m

Then insert Sto-Backing Rod.

Following an airing time of 60 minutes (+23°C), apply StoSeal F 355 or StoSeal F 505.

Delivery				
Packaging	tin			
	Article number	Name	Container	
	01829-004	StoSeal P 505	1 piece tin	

Identification

Safety

This product is subject to compulsory labelling in accordance with the current EU regulation. Observe the Safety Data Sheet!



Technical Data Sheet StoSeal P 505

Special notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use. Applications not specifically mentioned in this Technical Data Sheet are permissible only after

prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

StoCretec GmbH Gutenbergstr. 6 D-65830 Kriftel

Tel.: +49 6192 401-104 Fax: +49 6192 401-105 stocretec@sto.com www.stocretec.de

Rev. no.: 1 / EN /StoCretec./. 01.11.2023 / PROD0851 / StoSeal P 505